ADEC08F86150LTC





		Lift		Lift	Volts	Clear	Clear	Overall	Overall	Overall	Overall	Overall	Overall	Base	Base	Kick-out is	Kick-out is	Kick-out is
		Weight		Capacity		Inside	Inside	Loader	Extension	Loader	Dimens	Loader	Loader	Plate	Plate	measured from	measured	measured
						Platform	Platform	Height	of Arc,	Width	ion of	Depth	Depth	length	Width	front of base	from the	from, front of
						Width	Length		from		outside	At	At			plate edge to	front of base	base plate
									stowed		lift	handrail	base			the closest	plate edge, to	edge to
Famil	y Model		FTG						position to		arms	height	with			point, for the	the Rotating	Rotating
									Maximum		Width		Cover			platform has	Pivot side	Pivot side
									Height				when			been lowered	arm or	arm or saddle
													folded			down 100mm	saddle, at	at 100mm
																from floor level	floor level	down
									mm									
		kg	mm	kg	V	mm	mm	mm		mm	mm	mm	mm	mm	mm	mm	mm	mm
E-Seri	ADEC08F86150LTC	146	800	400kg	12V	860	1500	1365	+ 20	1215	1090	498	485	1112	325	362	410	415

All measurements are to be used as a guide as slight variations may occur between all units

Quick Facts

Two piece folding expanded mesh platform • 400kg lifting capacity • Illuminated platform • Easy access integrated manual back-up pump and handle • Durable hand-held control unit • Dual handles to assist with standee and wheelchair users • Lift-Tite system automatically secures the platform when in

transit • Durable ripple black finish • Side or rear door application • Electrohydraulic power up/gravity down operation • Mechanically operated outboard barrier • Equipped with adjustable anti-rattle features to suppress noise during transit • Tramanco colours • Safety yellow automatic mechanical in-board